

TrakkaCam[®] TC-300-SWIR



A NEW GENERATION OF COMPACT HIGH-PERFORMANCE MULTI SENSOR SURVEILLANCE SYSTEMS

Ideally suited for a variety airborne missions including fire detection and mapping, search and rescue, law enforcement, civil protection, military ISR and force protection, manned and unmanned platforms and installations.

TRAKKA SYSTEMS TC SERIES

The new TC series from Trakka Systems features advanced technology in an ergonomic industrial design that sets new standards for compact, high-performance, multispectral imaging in a non-ITAR, single-LRU configuration.

TC-300-SWIR's shortwave IR camera is uniquely suited to penetrate the most challenging atmospheric conditions such as haze, mist, fog, high humidity, rain, smog, and smoke, making it ideal for firefighting applications, and missions with degraded atmospheric conditions.

The EO/IR sensors are augmented with sophisticated image processing, allowing users to see through conditions such as fog, haze, low light, and total darkness. Image blending provides the ability to exploit imagery from the different sensors and extract details that would otherwise go undetected by a single sensor. A host of image processing features to improve operator performance and reduce workload, such as Moving Target Detection, are embedded right into the system.

The TC-300-SWIR enables operators and command centers to share mission-critical information in real-time while providing enhanced situational awareness via augmented reality overlays or pure synthetic views.

KEY BENEFITS

- Performance better than 10" competitors, and approaching that of bigger systems, but at lower price / lower mass
- Advanced sensors, superior in size class:
 - Available with a full suite of 7 payload options: (IR, SWIR, HDTV, LP, LRF, A/T, IMU/GPS)
 - Continuous optical zoom on all imaging channels for maximum situational awareness
 - Open upgradeable architecture for incorporation of new technology sensors
- The advanced real-time digital HD image processing engine is embedded into the gimbal and requires no additional electronics unit
- Moving Target Indicator (MTI) is embedded directly into the system
- High performance 4-axis active gyro stabilization with integrated 6-axis passive isolation for superior image stabilization
- Fully integrated IMU/INS providing Geo-Location and Geo Hold, with easy Moving Maps integration
- Innovative and ergonomic system design provides flexible platform and installation options
- Compact Single-LRU configuration is easy to install, integrate and requires no junction box
- Non-ITAR exportable product
- RTCA DO-160 Tested for Environmental, Electromagnetic and Mechanical compliance, and capable of withstanding the harshest environments



TC-300-SWIR

GIMBAL SPECIFICATIONS

Weight	~22 kg (48.5 lb)
Diameter	300mm (11.8")
Azimuth	Continuous Azimuth
Elevation	+20 to -120 Elevation (+90 Stow)
Stabilization	4 axis, active gyro-stabilization with integrated 6 axis passive isolation

THERMAL IMAGER

Type	3-5µm MWIR array
Resolution	1280 x 720
Fields of View	40° to 2.4°, continuous zoom

HDTV CAMERA

Type	HD CMOS Global Shutter
Resolution	3.2 MPixels
Fields of View	35° to 1.3°, continuous zoom
LLTV Mode	Yes

SWIR

Type	InGaAs Photodiode Array
Resolution	640x512
Fields of View	47° to 7.0°, continuous zoom

LASER RANGE FINDER (OPTIONAL)

Wavelength	1535 nm, Eye-safe
Range	12km
Repetition Rate	0.5 Hz or Single-Shot Modes

LASER POINTER (OPTIONAL)

Type	Class 3B
Wavelength	830nm
Output Power	80mW

ELECTRICAL REQUIREMENTS

Max power	320W Maximum Power
Steady State Power	100W Steady State
Input Voltage	22-36V Wide-Range Input Voltage

OPTIONS

Interface Types	SMPT E HD video outputs and H.264/H.265 over Ethernet (MISB 0601.7 Compliant), RS422, RS232
Functional Interfaces & Features	Auto Tracking, Geo-Location with integrated IMU/INS, Metadata, Moving Maps & Augmented Reality, Remote Control, Searchlight Slaving, Radar Slaving, AIS and other NMEA 0183 Interfaces, Data Links & Video Downlinks

ENVIRONMENTAL

Standards	MIL-STD 461, MIL-STD 810, RTCA DO-160, IP 66
-----------	--

Note: All FOVs are 720p



FEATURES

- Moving Target Indicator (option)
- Object Tracking / Scene Tracking Modes (option)
- EO De-Fog (Haze Penetration) Processing
- Digital Contrast Enhancement
- Local Area Contrast Processing
- Edge Sharpening
- Image Noise Reduction
- Picture in Picture / Split screen
- 4x Electronic Continuous Zoom
- Graphical On-Screen Display for Intuitive Operation

Trakka Corp Pty Ltd

23 Kilpa Road, Moorabbin
Victoria 3189 Australia
Phone: +61 3 9553 3000

Trakka Systems AB

Stationsvägen 46
635 36 Årla Sweden
Phone: +46 16 708 60

Trakka USA LLC

4725 Lena Road, Unit 103
Bradenton Florida 34211, USA
Phone: +1 941 500-5158

trakkasystems.com

info@trakkasystems.com

