

TrakkaCam[®] TC-375G



THE NEXT GENERATION OF HIGH-PERFORMANCE, LONG-RANGE MULTI SENSOR SURVEILLANCE SYSTEMS

Ideally suited for a variety of long-range land missions including; Border Security, Law enforcement, Counter-terrorism operations, C-UAS, Military reconnaissance, Military Force Protection, Disaster relief among others.

TRAKKA SYSTEMS TC SERIES

The new TC series from Trakka Systems features advanced technology in an ergonomic industrial design that sets new standards for full HD (1080p), long-range, multispectral imaging in a non-ITAR single-LRU configuration.

The TrakkaCam[®] TC-375G is MIL tested and built to withstand the harshest environmental conditions and operations. The system's long-range EO/IR sensors are augmented with sophisticated image processing, to see through conditions such as fog, haze, low light, and total darkness.

An advanced, high-speed, digital video engine is embedded directly within the single-LRU gimbal delivering several standard and optional functions, such as Moving Target Indicator (MTI) with Drone Detection Mode, reducing operator workload and increasing system performance under adverse conditions.

All systems can be interfaced with moving map systems, maritime radar systems, Automatic Identification Systems (AIS), and secure data links. These attributes enable operators and command centers to share mission-critical information in real-time while providing enhanced situational awareness via augmented reality overlays or pure synthetic views.

KEY BENEFITS

- Optimized for maritime operations
- Advanced sensors, superior in size class:
 - Available with a full suite of 8 Payload options: (HD MWIR, HDTV Spotter, SWIR or LLTV, LRF, LP, LI,A/T, IMU/Dual GPS)
 - Continuous optical zoom on all imaging channels for maximum situational awareness
 - Open upgradeable architecture for incorporation of new technology sensors
 - Advanced multi-mode Auto Tracker
- Moving Target Detection (MTI) embedded directly into the system
- High performance 4-axis active gyro stabilization with integrated 6-axis passive isolation for superior image stabilization
- Fully Integrated IMU/INS with dual GPS capability for static navigation operations
- Embedded H.264/ H.265 video over ethernet with MISB 0601.7 Compliant Metadata. No need for separate encoder.
- Innovative and ergonomic system design provides flexible platform and installation options
- Compact Single-LRU configuration is easy to install, integrate and requires no junction box
- Non-ITAR, widely exportable product
- MIL-STD & IP66 Tested for Environmental, Electromagnetic and Mechanical compliance, and capable of withstanding the harshest environments



TC-375G

GIMBAL SPECIFICATIONS

Weight	<45 kg (99lb)
Diameter	375mm (14.7")
Azimuth	Continuous Azimuth
Elevation	-20° to +120° Elevation
Stabilization	4 axis, active gyro-stabilization with integrated 6 axis passive isolation

THERMAL IMAGER

Type	3-5µm MWIR array
Resolution	1280 x 1024 (15µm) *Optional 1280x720 (10µm)
Fields of View	38° to 1.29° *Optional 15° to 1.25°

COLOR HDTV (SPOTTER)

Type	HD CMOS Global Shutter
Resolution	3.2 MPixels
Fields of View	24° to 0.33°

LOW LIGHT HD CAMERA (OPTIONAL)

Type	HD CMOS Global Shutter
Resolution	2.37 MPixels
Fields of View	35° to 1.3°

SWIR (OPTIONAL)

Resolution	1280 x 1024 pixels
Fields of View	28.7° to 2.9°, continuous zoom

LASER RANGE FINDER (OPTIONAL)

Wavelength	1535 nm, Eye-safe
Range	20km
Repetition Rate	0.5Hz or Single-Shot Modes

LASER POINTER (OPTIONAL)

Type	Class 3B
Wavelength	830nm
Output Power	200mW

LASER ILLUMINATOR (OPTIONAL)

Type	Class 3B
Wavelength	860nm
Output Power	450mW

ELECTRICAL REQUIREMENTS

Power Requirements	<280W average (<350W max)
Input Voltage	22-36V Wide-Range Input Voltage

OPTIONS

Interface Types	SMPTE HD video outputs and H.264/H.265 over Ethernet (MISB 0601.7 Compliant), RS422, RS232
Functional Interfaces & Features	Auto Tracking, Geo-Location with integrated IMU/INS, Interface to Aircraft INS/GPS, Metadata, Moving Maps & Augmented Reality, Remote Control, Searchlight Slaving, Radar Slaving, Data Links & Video Downlinks

ENVIRONMENTAL

Standards	MIL-STD 461, MIL-STD 810, RTCA DO-160, IP 66, IEC 60945
-----------	---



FEATURES

- Moving Target Indicator (option)
- Target Tracking / Scene Tracking Modes (option)
- Image Blending (option)
- EO De-Fog (Haze Penetration) Processing
- 4x Electronic Continuous Zoom
- Digital Contrast Enhancement
- Local Area Contrast Processing
- Pseudo Color IR Palettes
- Edge Sharpening
- Image Noise Reduction
- Picture in Picture / Split screen
- Graphical On-Screen Display for Intuitive Operation

Trakka Corp Pty Ltd

23 Kilpa Road, Moorabbin
Victoria 3189 Australia
Phone: +61 3 9553 3000

Trakka Systems AB

Stationsvägen 46
635 36 Årila Sweden
Phone: +46 16 708 60

Trakka USA LLC

4725 Lena Road, Unit 103
Bradenton Florida 34211, USA
Phone: +1 813 815-4321

trakkasystems.com

info@trakkasystems.com

Note: All FOVs are 720p. This information is provided for reference only. Specifications are subject to change without notice.
Copyright and all rights reserved. 10092024

